


N-Channel 1.25-W, 2.5-V MOSFET

PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
20	0.085 @ $V_{GS} = 4.5$ V	2.8
	0.115 @ $V_{GS} = 2.5$ V	2.4



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)			
Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	± 8	
Continuous Drain Current ($T_J = 150^\circ\text{C}$) ^b	$T_A = 25^\circ\text{C}$	2.8	A
	$T_A = 70^\circ\text{C}$	2.2	
Pulsed Drain Current ^a	I_{DM}	10	
Continuous Source Current (Diode Conduction) ^b	I_S	1.6	
Power Dissipation ^b	$T_A = 25^\circ\text{C}$	1.25	W
	$T_A = 70^\circ\text{C}$	0.80	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 150	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS			
Parameter	Symbol	Limit	Unit
Maximum Junction-to-Ambient ^b	R_{thJA}	100	$^\circ\text{C/W}$
Maximum Junction-to-Ambient ^c		166	

Notes

- a. Pulse width limited by maximum junction temperature.
- b. Surface Mounted on FR4 Board, $t \leq 5$ sec.
- c. Surface Mounted on FR4 Board.

For SPICE model information via the Worldwide Web: <http://www.vishay.com/www/product/spice.htm>



SPECIFICATIONS (T _A = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 10 μA	20			V
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 50 μA	0.65			
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±8 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20 V, V _{GS} = 0 V			1	μA
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 55 °C			10	
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 4.5 V	6			A
		V _{DS} ≥ 5 V, V _{GS} = 2.5 V	4			
Drain-Source On-Resistance ^a	r _{DS(on)}	V _{GS} = 4.5 V, I _D = 3.6 A		0.07	0.085	Ω
		V _{GS} = 2.5 V, I _D = 3.1 A		0.085	0.115	
Forward Transconductance ^a	g _{fs}	V _{DS} = 5 V, I _D = 3.6 A		10		S
Diode Forward Voltage	V _{SD}	I _S = 1.6 A, V _{GS} = 0 V		0.76	1.2	V
Dynamic						
Total Gate Charge	Q _g	V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 3.6 A		5.4	10	nC
Gate-Source Charge	Q _{gs}			0.65		
Gate-Drain Charge	Q _{gd}			1.60		
Input Capacitance	C _{iss}	V _{DS} = 10 V, V _{GS} = 0 V, f = 1 MHz		340		pF
Output Capacitance	C _{oss}			115		
Reverse Transfer Capacitance	C _{rss}			33		
Switching						
Turn-On Delay Time	t _{d(on)}	V _{DD} = 10 V, R _L = 5.5 Ω I _D ≅ 3.6 A, V _{GEN} = 4.5 V, R _G = 6 Ω		12	25	ns
Rise Time	t _r			36	60	
Turn-Off Delay Time	t _{d(off)}			34	60	
Fall-Time	t _f			10	25	







Notes

a. Pulse test: PW ≤ 300 μs duty cycle ≤ 2%.

VNLR02








TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)





TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.